

OPTICAL FIBER AND SYSTEM CONTAINING SAME

Technical Field

The invention relates to optical fibers (e.g., fiber amplifiers and fiber lasers), and systems containing optical fibers (e.g., fiber amplifier systems and fiber laser systems).

Background

Certain optical fibers can be used as fiber amplifiers or fiber lasers.

Fiber amplifiers are typically used to amplify an input signal. Often, the input signal and a pump signal are combined and passed through the fiber amplifier to amplify the signal at the input wavelength. The amplified signal at the input wavelength can then be isolated from the signal at undesired wavelengths.

Raman fiber lasers can be used, for example, as energy sources. In general, Raman fiber lasers include a pump source coupled to a fiber, such as an optical fiber, having a gain medium with an active material. Energy emitted from the pump source at a certain wavelength λ_p , commonly referred to as the pump energy, is coupled into the fiber. As the pump energy interacts with the active material in the gain medium of the fiber, one or more Raman Stokes transitions can occur within the fiber, resulting in the formation of energy within the fiber at wavelengths corresponding to the Raman Stokes shifts that occur (e.g., λ_{s1} , λ_{s2} , λ_{s3} , λ_{s4} , etc.).

Typically, a Raman fiber laser is designed so that the energy formed at one or more Raman Stokes shifts is substantially confined within the fiber. This can enhance the formation of energy within the fiber at one or more higher order Raman Stokes shifts. Often, the fiber is also designed so that at least a portion of the energy at wavelengths corresponding to predetermined, higher order Raman Stokes shifts (e.g., λ_{sx} , where x is equal to or greater than one) is allowed to exit the fiber.

Summary

In general, the invention relates to optical fibers (e.g., fiber amplifiers and fiber lasers), and systems containing optical fibers (e.g., fiber amplifier systems and fiber laser systems).

In one aspect, the invention features a fiber (e.g., a fiber laser or a fiber amplifier). The fiber includes an optical fiber having a first section and a second section coupled to the first section. The first section has a gain medium including a first active material, and the second section has a gain medium including a second active material. The second active material can be the same as or different than the first active material. The optical fiber also includes a first reflector disposed in the first section of the optical fiber. The first reflector is configured to reflect substantially all energy impinging thereon at a first wavelength. The optical fiber further includes a second reflector disposed in the optical fiber outside the first section of the optical fiber. The second reflector is configured to reflect substantially all energy impinging thereon at the first wavelength.

In another aspect, the invention features a system that includes an energy source capable of emitting energy at a pump wavelength and a fiber (e.g., a fiber amplifier or a fiber laser). The fiber includes an optical fiber having a first section and a second section coupled to the first section. The first section has a gain medium including a first active material, and the second section has a gain medium including a second active material. The second active material can be the same as or different than the first active material. The optical fiber also includes a first reflector disposed in the first section of the optical fiber. The first reflector is configured to reflect substantially all energy impinging thereon at a first wavelength. The optical fiber further includes a second reflector disposed in the optical fiber outside the first section of the optical fiber. The second reflector is configured to reflect substantially all energy impinging thereon at the first wavelength. The energy source and the optical fiber are configured so that energy at the pump wavelength emitted by the energy source can be coupled into the optical fiber.

In another aspect, the invention features a fiber (e.g., a fiber amplifier or a fiber laser). The fiber includes an optical fiber having a first section and a second section spliced to the first section. The first section has a gain medium including a first active material, and the second section has a gain medium including a second active material. The second active material can be the same as or different than the first active material. The optical fiber also includes a first reflector disposed in the first section of the optical fiber, and the first reflector is configured to reflect substantially all energy impinging

thereon at a first wavelength. The optical fiber further includes second reflector disposed in the second section of the optical fiber, and the second reflector is configured to reflect substantially all energy impinging thereon at the first wavelength. In addition, the optical fiber includes a third reflector disposed in the second section of the optical fiber. The third reflector is configured to partially reflect energy impinging thereon at a second wavelength different than the first wavelength. The optical fiber also includes a fourth reflector disposed in the second section of the optical fiber and between the first and third reflectors. The fourth reflector is configured to reflect substantially all energy impinging thereon at the second wavelength.

In a further aspect, the invention features a fiber system (e.g., a fiber laser system or a fiber amplifier system). The system includes an energy source capable of emitting energy at a pump wavelength and a fiber. The fiber includes an optical fiber having a first section and a second section spliced to the first section. The first section has a gain medium including a first active material, and the second section has a gain medium including a second active material. The second active material can be the same as or different than the first active material. The optical fiber also includes a first reflector disposed in the first section of the optical fiber, and the first reflector is configured to reflect substantially all energy impinging thereon at a first wavelength. The optical fiber further includes second reflector disposed in the second section of the optical fiber, and the second reflector is configured to reflect substantially all energy impinging thereon at the first wavelength. In addition, the optical fiber includes a third reflector disposed in the second section of the optical fiber. The third reflector is configured to partially reflect energy impinging thereon at a second wavelength different than the first wavelength. The optical fiber also includes a fourth reflector disposed in the second section of the optical fiber and between the first and third reflectors. The fourth reflector is configured to reflect substantially all energy impinging thereon at the second wavelength. The energy source and the optical fiber are configured so that energy at the pump wavelength emitted by the energy source can be coupled into the optical fiber.

In one aspect, the invention features a fiber (e.g., a fiber amplifier or a fiber laser) including an optical fiber having N sections. The N sections are coupled together. At

least one of the N sections of the optical fiber has a gain medium with an active material. The optical fiber also includes a plurality of reflectors disposed in the optical fiber. N is an integer having a value of at least three.

N can be, for example, 3, 4, 5, 6, 7, 8, 9 or 10.

At least two of the N sections of the optical fiber can have a gain medium with an active material. The active material in one of the at least two of the N sections of the optical fiber can be different than an active material of another of the N sections of the optical fiber having a gain medium.

Each of the N sections of the optical fiber have a gain medium with an active material.

The optical fiber can have a first section with an end configured to receive energy at a wavelength λ_p . The first section of the optical fiber can have a first reflector disposed therein. The first reflector can be configured to reflect substantially all energy impinging thereon at a wavelength λ_{s1} , where $\lambda_{s1}^{-1} = \lambda_p^{-1} - \lambda_{r1}^{-1}$, (c/λ_{r1}) is the Raman Stokes shift frequency for an active material in a gain medium in the first section of the optical fiber, and c is the speed of light.

The optical fiber can have an N^{th} section with an end opposite the end of the first section. The N^{th} section of the optical fiber can have a first reflector disposed therein. The first reflector can be configured to reflect substantially all energy impinging thereon at a wavelength λ_{s1n} , where $\lambda_{s1n}^{-1} = \lambda_{s1(n-1)}^{-1} - \lambda_{rn}^{-1}$, and (c/λ_{rn}) is the Raman Stokes shift frequency for an active material in a gain medium in the N^{th} section of the optical fiber.

The Nth section of the optical fiber can have a second reflector disposed therein. The second reflector can be configured to partially reflect energy impinging thereon at the wavelength λ_{s1n} .

The Nth section of the optical fiber can have a third reflector disposed therein. The third reflector can be configured to reflect substantially all energy impinging thereon at the wavelength $\lambda_{s1(n-1)}$, where $\lambda_{s1(n-1)}^{-1} = \lambda_{s1(n-2)}^{-1} - \lambda_{r(n-1)}^{-1}$, and ($c/\lambda_{r(n-1)}$) is the Raman Stokes shift frequency for the active material in the $(N-1)^{\text{th}}$ section of the fiber.

Each of the remaining sections of the optical fiber can have two reflectors disposed therein. One of the reflectors disposed in each of the remaining sections of the

wavelength λ_{s1m} , where $\lambda_{s1m}^{-1} = \lambda_{s1(m-1)}^{-1} - \lambda_{rm}^{-1}$, $\lambda_{s1(m-1)}$, and (c/λ_{rm}) is the Raman Stokes shift frequency for an active material in the section of the fiber.

The other reflectors can be disposed in each of the remaining sections of the optical fiber and configured to reflect substantially all energy impinging thereon at a wavelength $\lambda_{s1(m-1)}$, where $\lambda_{s1(m-1)}^{-1} = \lambda_{s1(m-2)}^{-1} - \lambda_{r(m-1)}^{-1}$, and $(c/\lambda_{r(m-1)})$ is the Raman Stokes shift frequency for an active material in an immediately preceding section of the optical fiber.

Each of the remaining sections of the optical fiber can have two reflectors disposed therein. One of the reflectors disposed in each of the remaining sections of the optical fiber can be configured to reflect substantially all energy impinging thereon at a wavelength λ_{s1m} , where $\lambda_{s1m}^{-1} = \lambda_{s1(m-1)}^{-1} - \lambda_{rm}^{-1}$, $\lambda_{s1(m-1)}$, and (c/λ_{rm}) is the Raman Stokes shift frequency for an active material in the section of the fiber.

In another aspect, the invention features a fiber system (e.g. a fiber amplifier system or a fiber laser system) that includes an energy source and a fiber. The fiber includes an optical fiber having N sections. The N sections are coupled together. At least one of the N sections of the optical fiber has a gain medium with an active material. The optical fiber also includes a plurality of reflectors disposed in the optical fiber. N is an integer having a value of at least three, and the energy source and the optical fiber are configured so that energy at a wavelength emitted by the energy source can be coupled into the optical fiber.

In a further aspect, the invention features a fiber (e.g., a fiber amplifier or a fiber laser) that includes an optical fiber having at least first and second sections coupled together. The first section has a first gain medium with a first active material, and the second section has a second gain medium with a second active material different. The second active material can be the same as or different than the first active material. The optical fiber is configured to be capable of receiving energy at a first wavelength and to be capable of outputting energy at a second wavelength longer than the first wavelength. The optical fiber also includes a plurality of reflectors disposed in the optical fiber. The plurality of optical fibers are configured so that energy propagating in the optical fiber at

the first wavelength undergoes at least one Raman Stokes shift to create energy in the optical fiber at the second wavelength, and so that, when the optical fiber receives energy at the first wavelength, a power output by the optical fiber at the second wavelength is at least about 55% of a power of the energy the optical fiber receives at that first wavelength.

In another aspect, the invention features an article, such as a fiber amplifier or a fiber laser, that includes an optical fiber having multiple sections. At least two of the fiber sections have gain media that containing different active materials. The number of sections can be, for example, 3, 4, 5, 6, 7, 8, 9 or 10. Each section can have a gain medium. The gain medium in each section can contain the same or different active material as the other sections of fiber. The article can be used in a system that includes an energy source (e.g., a laser) capable of emitting energy that can be coupled into the fiber.

In some embodiments, the invention can provide a Raman fiber laser having a relatively high output power at a desired wavelength (e.g., at least about 0.1 Watt, at least about 0.5 Watt, at least about one Watt, at least about 2 Watts, at least about 5 Watts, at least about 10 Watts). Such a Raman fiber laser can operate, for example, under conditions of relatively high pump power (e.g., at least about 0.1 Watt, at least about 0.5 Watt, at least about one Watt, at least about 2 Watts, at least about 5 Watts, at least about 10 Watts).

In certain embodiments, the invention can provide a Raman fiber laser having a relatively low output power at one or more undesired wavelengths (e.g., less than about one Watt, less than about 0.5 Watt, less than about 0.1 Watt, less than about 0.05 Watt). Such a Raman fiber laser can operate, for example, under conditions of relatively high pump power (e.g., at least about 0.1 Watt, at least about 0.5 Watt, at least about one Watt, at least about 2 Watts, at least about 5 Watts, at least about 10 Watts).

In some embodiments, the invention can provide a Raman fiber laser than can convert energy entering the Raman fiber laser at a particular wavelength (e.g., a pump wavelength) to energy exiting the Raman fiber laser at a different wavelength (e.g., a desired wavelength) with relatively high efficiency (e.g., an efficiency of: at least about

35%, at least about 40%, at least about 45%, at least about 50%, at least about 55%, at least about 60%, at least about 65%, at least about 70%, at least about 75%, at least about 80%, at least about 85%, at least about 90%, at least about 95%, at least about 98%).

In certain embodiments, the invention can provide a Raman fiber laser that can convert energy entering the Raman fiber laser at a particular wavelength (e.g., a pump wavelength) to energy exiting the Raman fiber laser at wavelengths other than a desired wavelength with relatively low efficiency (e.g., an efficiency of: at most about 45%, at most about 40%, at most about 35%, at most about 30%, at most about 25%, at most about 20%, at most about 15%, at most about 10%, at most about 5%, at most about 2%).

The Raman fiber lasers can provide these properties when the difference between the pump energy and the output energy is any value (e.g., relatively small or relatively large). In some embodiments, the difference between the pump energy and the output energy can be relatively large (e.g., at least about 100 cm^{-1} , at least about 200 cm^{-1} , at least about 500 cm^{-1} , at least about $1,000\text{ cm}^{-1}$, at least about $1,250\text{ cm}^{-1}$, at least about $1,500\text{ cm}^{-1}$, at least about $1,750\text{ cm}^{-1}$, at least about $2,000\text{ cm}^{-1}$).

In certain embodiments, the fibers can be used as amplifiers rather than lasers.

Features, objects and advantages of the invention are in the description, drawings and claims.

Description of Drawings

Fig. 1 is a schematic representation of an embodiment of a Raman fiber laser system;

Figs. 2A and 2B are cross-sectional views of sections of an optical fiber;

Figs. 3A-3C are graphs demonstrating the power at three different wavelengths in an optical fiber contained in an embodiment of a Raman fiber laser system;

Fig. 4 is a schematic representation of an embodiment of a Raman fiber laser system;

Fig. 5 is a schematic representation of an embodiment of a Raman fiber laser system;

Fig. 6 is a schematic representation of an embodiment of a Raman fiber laser system;

Fig. 7 is a schematic representation of an embodiment of a Raman fiber laser system;

Fig. 8 is a schematic representation of an embodiment of a Raman fiber laser system;

Fig. 9 is a schematic representation of an embodiment of a Raman fiber laser system;

Fig. 10 is a schematic representation of an embodiment of a Raman fiber laser system;

Fig. 11 is a schematic representation of an embodiment of a Raman fiber laser system;

Fig. 12 is a schematic representation of an embodiment of a Raman fiber laser system;

Fig. 13 is a schematic representation of an embodiment of a Raman fiber laser system; and

Fig 14 is a schematic representation of an embodiment of a fiber amplifier system.

Detailed Description

Fig. 1 shows an embodiment of a Raman fiber laser system 100 including an optical fiber 110 and a laser 120. Laser 120 is configured so that energy emitted by laser 120 at a wavelength λ_p is coupled into optical fiber 110. Optical fiber 110 has a first section 130 having a gain medium containing an active material and a second section 140 having a gain medium containing a different active material. Examples of active materials include GeO_2 , P_2O_5 , SiO_2 , B_2O_3 , SiO_xF_y , and the like. Sections 130 and 140 of optical fiber 110 are spliced together at region 150.

Figs. 2A and 2B are cross-sectional views of sections 130 and 140, respectively, of optical fiber 110. As shown in Fig. 2A, section 130 has a gain medium 210 containing an active material, a cladding 220 (e.g., a fused silica layer) and an additional layer 230 (e.g., a polymer layer). As shown in Fig. 2B, section 140 has a gain medium 215 containing an active material, a cladding 225 (e.g., a fused silica layer) and an additional layer 235 (e.g., a polymer layer). Although Figs. 2A and 2B show a particular design of

optical fiber 110, other designs of appropriate optical fibers are known to those skilled in the art and are contemplated.

Referring to Fig. 1, optical fiber 110 also includes a first pair of reflectors 160 and 170 (e.g., a pair of fiber Bragg gratings), and a second pair of reflectors 180 and 190 (e.g., a pair of fiber Bragg gratings). Reflectors 160 and 170 are designed to reflect substantially all (e.g., about 100%) energy impinging thereon at a wavelength λ_{s1} , where $\lambda_{s1}^{-1} = \lambda_p^{-1} - \lambda_r^{-1}$, (c/λ_r) is the Raman Stokes shift frequency for the active material in gain medium 210, and c is the speed of light.

Reflector 180 is designed to reflect substantially all (e.g., about 100%) energy impinging thereon at wavelength λ_{s1} , and reflector 190 is designed to reflect a portion (e.g., less than about 98%, less than about 95%, less than about 90%, less than about 80%, less than about 70%, less than about 60%, less than about 50%, less than about 40%, less than about 30%, less than about 20%, less than about 10%) of energy impinging thereon at wavelength λ_{s1} , where $\lambda_{s1}^{-1} = \lambda_{s1}^{-1} - \lambda_r^{-1}$ and (c/λ_r) is the Raman Stokes shift frequency for the active material in gain medium 215.

Section 130 of optical fiber 110 further includes a reflector 310 (e.g., a fiber Bragg grating). Reflector 310 is designed to reflect substantially all (e.g., about 100%) energy propagating in section 130 at λ_p , which reduces (e.g., eliminates) the propagation of energy at λ_p in section 140 of fiber 110.

Section 130 of optical fiber 110 also includes a suppressor 410. Suppressor 410 is designed to suppress the formation of higher order Raman Stokes shifts for the active material in section 130 of fiber 110 (e.g., one or more of λ_{s2} , λ_{s3} , λ_{s4} , etc.).

With this arrangement, as energy at wavelength λ_p enters optical fiber 110, the energy propagates through section 130 until it impinges upon reflector 310, where it is reflected and propagates through section 130 in the reverse direction so that substantially no energy at wavelength λ_p enters section 140 of fiber 110. Reflector 310 can increase the amount of energy at λ_{s1} propagating in fiber 110 (relative to an otherwise substantially similar system without reflector 310) by increasing the effective optical length of energy at λ_p in section 130 of fiber 110, which, in turn, can increase the amount of energy at λ_{s1} propagating in section 140 of fiber 110 (see discussion below). Reflector

310 can also decrease the formation of energy at wavelength λ_u , where $\lambda_u^{-1} = \lambda_p^{-1} - \lambda_r^{-1}$ (see discussion below).

As energy at wavelength λ_p propagates through section 130 in the forward and reverse directions, it creates energy at wavelength λ_{s1} . Energy at wavelength λ_{s1} propagates through sections 130 and 140 until it reaches reflector 170 where it is reflected by reflector 170. Energy at wavelength λ_{s1} then propagates through sections 140 and 130 in the reverse direction until it reaches reflector 160 where it is reflected forward through sections 130 and 140. Energy at wavelength λ_{s1} continues to propagate in fiber 110 in the forward and in reverse directions between reflectors 160 and 170.

As energy at wavelength λ_{s1} propagates through section 130 of fiber 110, it can impinge upon suppressor 410, which reduces (e.g., substantially eliminates) the transfer of energy at wavelength λ_{s1} to energy at wavelength λ_{s2} (and/or energy at higher order Raman Stokes shifts for the active material in gain medium 210). In some embodiments, suppressor 410 is a long period gratings (LPG) having a resonance frequency of (c/λ_{s2}) , where $\lambda_{s2}^{-1} = \lambda_{s1}^{-1} - \lambda_r^{-1}$. The LPG can couple energy at wavelength λ_{s2} that impinges thereon out of gain medium 210 and into cladding 220. Cladding 220 can be formed of a material (e.g., fused silica) that dissipates energy at λ_{s2} relatively quickly. This can suppress the power of wave λ_{s2} propagating in fiber 110, which correspondingly can suppress the formation of energy at higher order Raman Stokes shifts propagating in fiber 110. The suppression of higher order Raman Stokes shift(s) can result in fiber 110 having a higher power of wave λ_{s1} propagating therein relative to a substantially similar system without suppressor 410. This, in turn, can increase the amount of energy at λ_{s1} propagating in section 140 of fiber 110 (see discussion below).

As energy at wavelength λ_{s1} propagates through section 140 of fiber 110, it creates energy at wavelength λ_{s1} . Energy at wavelength λ_{s1} propagating in section 140 in the reverse direction is reflected by reflector 180 and then propagates through section 140 in the forward direction. Energy at wavelength λ_{s1} propagating through section 140 in the forward direction impinges on reflector 190. Some of the energy at wavelength λ_{s1} impinging on reflector 190 is reflected by reflector 190 and then propagates through

section 140 in the reverse direction, and some of the energy at wavelength λ_{s1} impinging on reflector 190 passes through reflector 190 and exits fiber 110.

Optical fiber 110 can convert energy entering fiber 110 at wavelength λ_p to energy exiting fiber 110 at wavelength λ_{s1} with relatively high efficiency. In certain embodiments, fiber 110 can convert at least about 35% (e.g., at least about 40%, at least about 45%, at least about 50%, at least about 55%, at least about 60%, at least about 65%, at least about 70%, at least about 75%, at least about 80%, at least about 85%, at least about 90%, at least about 95%, at least about 98%) of the energy entering fiber 110 at wavelength λ_p to energy exiting fiber 110 at wavelength λ_{s1} .

Optical fiber 110 can convert energy entering fiber 110 at wavelength λ_p to energy exiting fiber 110 at wavelengths other than λ_{s1} with relatively low efficiency. In certain embodiments, fiber 110 can convert at most about 45% (e.g., at most about 40%, at most about 35%, at most about 30%, at most about 25%, at most about 20%, at most about 15%, at most about 10%, at most about 5%, at most about 2%) of the energy entering fiber 110 at wavelength λ_p to energy exiting fiber 110 at wavelengths other than λ_{s1} .

Without wishing to be bound by theory, it is believed that these characteristics of fiber 110 can be explained using the following system of nonlinear differential equations.

$$\begin{aligned}\frac{dI_p^+}{dz} &= -g_p(I_{\lambda_{s1}}^+ + I_{\lambda_{s1}}^-) \times I_p^+ - \alpha_p I_p^+ = -\frac{dI_p^-}{dz} \\ \frac{dI_{\lambda_{s1}}^+}{dz} &= g_1 I_{\lambda_{s1}}^+ \times (I_p^+ + I_p^-) - \alpha_1 I_{\lambda_{s1}}^+ - g_1' I_{\lambda_{s1}}^+ \times (I_{\lambda_{s1}}^+ + I_{\lambda_{s1}}^-) = -\frac{dI_{\lambda_{s1}}^-}{dz} \\ \frac{dI_{\lambda_{s1}'}^+}{dz} &= g_1' I_{\lambda_{s1}'}^+ \times (I_{\lambda_{s1}}^+ + I_{\lambda_{s1}}^-) - \alpha_1' I_{\lambda_{s1}'}^+ = -\frac{dI_{\lambda_{s1}'}^-}{dz}\end{aligned}$$

The indices $^+$ and $^-$ represent propagation in fiber 110 from left to right and from right to left, respectively. I_p , $I_{\lambda_{s1}}$, and $I_{\lambda_{s1}'}$ represent the intensities of energy propagating in fiber 110 at wavelengths λ_p , λ_{s1} and λ_{s1}' , respectively. α_p , α_1 and α_1' are the loss coefficients of energy propagating in fiber 110 at wavelengths λ_p , λ_{s1} and λ_{s1}' , respectively, due to, for example, imperfections, scattering and/or splicing in fiber 110. g_p , g_1 and g_1' are the Raman gain coefficients, respectively, of energy propagating in fiber

110 at wavelengths λ_p , λ_{s1} and $\lambda_{s1'}$, respectively, due to power gain via stimulated Raman scattering (SRS). g'_1 is the Raman gain coefficient for the transfer of energy from λ_{s1} to $\lambda_{s1'}$. $g'_1 = (\lambda_{s1}/\lambda_{s1'})(A_{s1}/A_{s1'})(g_1)$, where A_{s2} is the effective area of the mode at wavelength λ_{s2} .

It is believed that for fiber 110 the second equation noted above can be decoupled into two systems of equations, with each system of equation being without a g'_1 term.

The first system of equations, which is believed to describe the propagation of energy in section 130 of fiber 110, can be written as:

$$\begin{aligned}\frac{dI_p^+}{dz} &= -g_0(I_{\lambda_{s1}}^+ + I_{\lambda_{s1}}^-) \times I_p^+ - \alpha_0 I_p^+ = -\frac{dI_p^-}{dz} \\ \frac{d\hat{I}_{\lambda_{s1}}^+}{dz} &= g_1 \hat{I}_{\lambda_{s1}}^+ \times (I_p^+ + I_p^-) - \alpha_1 \hat{I}_{\lambda_{s1}}^+ = -\frac{d\hat{I}_{\lambda_{s1}}^-}{dz}.\end{aligned}$$

The second system of equations, which is believed to describe the propagation of energy in section 140 of fiber 110, can be written as:

$$\begin{aligned}\frac{d\tilde{I}_{\lambda_{s1}}^+}{dz} &= -\tilde{g}_1 \tilde{I}_{\lambda_{s1}}^+ \times (I_{\lambda_{sr}}^+ + I_{\lambda_{sr}}^-) - \tilde{\alpha}_1 \tilde{I}_{\lambda_{s1}}^+ = -\frac{d\tilde{I}_{\lambda_{s1}}^-}{dz} \\ \frac{d\tilde{I}_{\lambda_{sr}}^+}{dz} &= g_2 \tilde{I}_{\lambda_{sr}}^+ \times (\tilde{I}_{\lambda_{s1}}^+ + \tilde{I}_{\lambda_{s1}}^-) - \alpha_2 \tilde{I}_{\lambda_{sr}}^+ = -\frac{d\tilde{I}_{\lambda_{sr}}^-}{dz}.\end{aligned}$$

Appropriate boundary conditions for a wave $I_{\lambda_{s1}}$ at splice point 150 are believed to be:

$$\hat{I}_{\lambda_{s1}}^+ = \tilde{I}_{\lambda_{s1}}^+ \quad \text{and} \quad \hat{I}_{\lambda_{s1}}^- = \tilde{I}_{\lambda_{s1}}^-.$$

Figs. 3A-3C are graphs of the calculated (based on the above-noted equations) energy distribution at wavelengths λ_p , λ_{s1} and $\lambda_{s1'}$, respectively, for fiber 110 in which section 130 is 100 meters long and the active material in the gain medium of section 130 is GeO_2 , and in which section 140 is 20 meters long and the active material in the gain

medium of section 140 is P_2O_5 . Reflectors 160 and 170 reflect 100% of energy impinging thereon at wavelength λ_{s1} . Reflector 180 reflects 100% of energy impinging thereon at wavelength $\lambda_{s1'}$, and reflector 190 reflects about 80% of energy impinging thereon at wavelength $\lambda_{s1'}$. The power at wavelength λ_p is 3 Watts upon entering optical fiber 110. Reflectors 180 and 310 are disposed immediately adjacent point 150.

Fig. 3A shows that the power of λ_p decreases as it propagates across section 130 from a value of three Watts upon entering fiber 110 to a value of about 0.5 Watt at point 150. The power of λ_p continues to decrease as it propagates in the reverse direction from point 150, reaching a value of about 0.1 Watt at the end of fiber 110 where the pump energy enters fiber 110.

Fig. 3B shows that the power of λ_{s1} increases as it propagates in the forward direction across section 130, starting at a value of about 2.3 Watts at the point where the pump energy enters fiber 110 and obtaining a value of about 3.5 Watts at point 150. The power of λ_{s1} increases as it propagates in the reverse direction, starting at a value of about 0.4 Watts at point 150 and obtaining a value of about 2.3 Watts at the point where the pump energy enters fiber 110.

A portion of the energy at wavelength λ_{s1} propagating in section 140 in both the forward and reverse directions is transferred to energy at wavelength $\lambda_{s1'}$. As a result, the power of λ_{s1} decreases as energy at wavelength λ_{s1} propagates in both the forward and reverse directions through section 140 (Figs. 3B and 3C).

Fig. 3C shows that the power of $\lambda_{s1'}$ increases as it propagates in the forward direction across section 140 from a value of about 10.8 Watts at point 150 to a value of about 12 Watts at the end of fiber 110. The power of $\lambda_{s1'}$ increases as it propagates across section 140 from a value of about 9.6 Watts at the end of fiber 110 to a value of about 10.8 Watts at point 150.

Fig. 4 shows an embodiment of a Raman fiber laser system 400 in which reflector 310 is not present in optical fiber 110. Eliminating reflector 310 may be desirable, for example, when the power of wave λ_p is sufficiently low enough at point 150 that the amount of energy created at λ_u does not substantially interfere with the desired performance of the system.

Fig. 5 shows an embodiment of a Raman fiber laser system 500 in which suppressor 410 is not present in optical fiber 110. Eliminating suppressor 410 may be desirable, for example, when the power of wave λ_{s1} is sufficiently low enough in section 130 of fiber 110 that the amount of energy created at λ_{s2} (and/or energy at higher order Raman Stokes shifts for the active material in gain medium 210) does not substantially interfere with the desired performance of the system.

Fig. 6 shows an embodiment of a Raman fiber laser system 600 in which neither reflector nor suppressor 410 are present in optical fiber 110.

Fig. 7 shows an embodiment of a Raman fiber laser system 700 that includes a suppressor 710 in section 140 of optical fiber 110. Suppressor 710 is designed to suppress the formation of energy at higher order Raman Stokes shifts for the active material in gain medium 215 (e.g., energy at one or more of λ_{s2} , λ_{s3} , λ_{s4} , etc.). Suppressor 710 can be, for example, an LPG having its resonance frequency at (c/λ_{s2}) , where $\lambda_{s2}^{-1} = \lambda_{s1}^{-1} - \lambda_p^{-1}$. The presence of suppressor 710 in section 140 may be desirable, for example, when the power of wave λ_{s1} in section 140 is sufficiently high that the power of wave λ_{s2} (and/or energy at higher order Raman Stokes shifts for the active material in gain medium 215) that would form in section 140 in the absence of suppressor 710 would substantially interfere with the desired performance of the system. System 700 can optionally include reflector 310 and/or suppressor 410.

While the systems represented in Figs. 1 and 3-7 have shown reflectors and/or suppressor(s) having particular locations within optical fiber 110, it is to be understood that these components can have different locations (relative locations and/or absolute locations) within fiber 110. For example, the relative positions of reflectors 170 and 190 can be reversed. As another example, reflector 310 can be located in section 140 of fiber 110. As an additional example, reflector 180 can be disposed in section 130 of optical fiber 110 (e.g., to the right or left of point 150), and/or reflectors 170 and 190 can be disposed to the right of section 140 (e.g., in another section of fiber spliced to the right of section 140 of fiber 110). Combinations of these configurations can be used. Other locations of reflectors and/or suppressor(s) in fiber 110 are also contemplated.

Fig. 8 shows an embodiment of a Raman fiber laser system 800 having an optical fiber 810. Optical fiber 810 has a first section 130 having a gain medium containing an active material, and a second section 140 having a gain medium containing an active material that can be different than the active material contained in the gain medium of section 130, and a third section 820 having a gain medium containing an active material that can be different than the active material contained in the gain medium of section 140. The active material in the gain medium of section 820 of fiber 810 can be the same as or different than the active material in the gain medium of section 130 of fiber 810. Sections 140 and 820 are spliced together at region 850.

Optical fiber 810 includes pairs of reflectors 160 and 170, 180 and 195, and also includes a pair of reflectors 830 and 840 (e.g., a pair of fiber Bragg gratings). Reflector 195 (e.g., a fiber Bragg grating) is designed to reflect substantially all (e.g., about 100%) energy at λ_{s1} . Reflector 830 is designed to reflect substantially all (e.g., about 100%) energy at wavelength λ_{s1}' , and reflector 840 is designed to reflect a portion (e.g., less than about 98%, less than about 95%, less than about 90%, less than about 80%, less than about 70%, less than about 60%, less than about 50%, less than about 40%, less than about 30%, less than about 20%, less than about 10%) of energy at wavelength λ_{s1}'' , where $\lambda_{s1}''^{-1} = \lambda_{s1}'^{-1} - \lambda_p^{-1}$ and (c/λ_p) is the Raman Stokes frequency shift for the active material in the gain medium section 820 of fiber 810.

With this arrangement, as energy at λ_p enters optical fiber 810, the energy propagates through section 130 and creates energy at wavelength λ_{s1} . Energy at λ_{s1} then propagates through sections 130 and 140 in the forward direction until it reaches reflector 170 where it is reflected backward through sections 140 and 130. Energy at λ_{s1} then propagates through sections 140 and 130 in the reverse direction until it reaches reflector 160 where it is reflected forward through sections 130 and 140. Energy at λ_{s1} continues to propagate in fiber 810 in the forward and reverse directions between reflectors 160 and 170.

As energy at λ_{s1} propagates through section 140 of fiber 810, it creates energy at wavelength λ_{s1}' . Energy at λ_{s1}' then propagates through sections 140 and 820 in the forward direction until it reaches reflector 195 where it is reflected backward through

sections 820 and 140. Energy at λ_{s1} then propagates through sections 820 and 140 in the reverse direction until it reaches reflector 180 where it is reflected forward through sections 140 and 820. Energy at λ_{s1} continues to propagate in fiber 810 in the forward and reverse directions between reflectors 180 and 195.

As energy at λ_{s1} propagates through section 820 of fiber 610, it creates energy at wavelength λ_{s1}' . Energy at wavelength λ_{s1}' propagating in section 820 in the reverse direction is reflected by reflector 830 and then propagates through section 820 in the forward direction. Energy at wavelength λ_{s1}' propagating through section 820 in the forward direction impinges on reflector 840. Some of the energy at wavelength λ_{s1}' impinging on reflector 840 is reflected by reflector 840 and then propagates through section 820 in the reverse direction, and some of the energy at wavelength λ_{s1}' impinging on reflector 840 passes through reflector 840 and exits fiber 810.

Fig. 9 shows a Raman fiber laser system 900 that includes reflector 310 in section 130 of fiber 810. Fig. 10 shows a Raman fiber laser system 1000 that includes a suppressor 410 in section 130 of fiber 810. Fig. 11 shows a Raman fiber laser system 1100 that includes a suppressor 1110 in section 140 of fiber 810. Suppressor 1110 can be, for example, an LPG with a resonance frequency of (c/λ_{s1}) . Fig. 12 shows a Raman fiber laser system 1200 having suppressors 410 and 1110, and reflector 310.

Fig. 13 shows an embodiment of a Raman fiber laser system 1300 that includes a suppressor 1310 in section 820 of optical fiber 110. Suppressor 1310 is designed to suppress the formation of energy at higher order Raman Stokes shifts (e.g., one or more of λ_{s2} , λ_{s3} , λ_{s4} , etc.). Suppressor 1310 can be, for example, an LPG having its resonance frequency at (c/λ_{s2}) , where $\lambda_{s2}^{-1} = \lambda_{s1}^{-1} - \lambda_p^{-1}$. The presence of suppressor 1310 in section 820 may be desirable, for example, when the power of wave λ_{s1} in section 820 is sufficiently high that the power of wave λ_{s2} (and/or energy at higher-order Raman Stokes shifts for the active material in the gain medium of section 820 of fiber 810) that would form in section 820 in the absence of suppressor 1310 would substantially interfere with the desired performance of the system. System 1300 can optionally include reflector 310, suppressor 410 and/or suppressor 1110.

While Figs. 8-13 show the reflectors and/or suppressor(s) having particular locations within optical fiber 810, it is to be understood that these components can have different locations (relative locations and/or absolute locations) within fiber 810. For example, the relative positions of reflectors 195 and 840 can be reversed. As another example, reflector 310 can be located in section 140 of fiber 810. As an additional example, reflector 170 can be disposed in section 820 of fiber 810. As a further example, reflector 180 can be disposed in section 130 of fiber 810. Combinations of these configurations can be used. Other locations of these components in fiber 810 are also contemplated.

While embodiments have been shown in which sections 130, 140 and 820 are spliced together, the invention is not limited in this sense. Generally, sections 130, 140 and/or 820 are spliced together if they are formed of different materials. When sections 130, 140 and 820 are formed of the same materials, splicing is not required.

While Raman fiber lasers and Raman fiber laser systems having an optical fiber with two or three sections have been described, the invention is not limited to these systems. In general, an optical fiber can have N sections, where N is an integer (e.g., 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, etc.).

Moreover, while Raman fiber lasers and Raman fiber laser systems have been described with particular arrangements of active material in their respective gain media, other arrangements are also possible. In general, each section of the optical fiber can have a gain medium with an active material which can be the same or different than the active material in the gain medium of the neighboring section(s) of the fiber. In some embodiments, all sections of the optical fiber have a gain medium with the same active material. In certain embodiments, each section of the optical fiber has a gain medium with a different active material than the active material in the gain medium of the other sections. In some embodiments, the active material in the gain medium of neighboring sections can alternate. For example, a three-section optical fiber can be formed in which the active material in the gain medium of the first and third sections is the same, and in which the active material in the gain medium in the middle section is different. Other arrangements are contemplated.

Furthermore, while Raman fiber lasers and Raman fiber laser systems have been described in which sections of the optical fiber are spliced together, the invention is not limited in this sense. Generally, the sections of fiber are coupled together so that energy can propagate therebetween. Typically, the sections of fiber are contiguous. For example, in some embodiments, two neighboring sections of the optical fiber can have an interferometric connection. In certain embodiments, two neighboring sections of the optical fiber can be connected by a lens (e.g., a Green lens).

A typical design of a Raman fiber laser having N sections of optical fiber is as follows. The section of fiber closest to where the pump energy at wavelength λ_p enters the fiber has a reflector designed to reflect substantially all (e.g., about 100%) energy at λ_{s1} . The section of fiber furthest (the Nth section of the fiber) from where the pump energy λ_p enters the fiber has three reflectors. One reflector is designed to partially reflect energy at λ_{s1n} (i.e., the desired wavelength of energy created by the system in the Nth section of the fiber), where $\lambda_{s1n}^{-1} = \lambda_{s1(n-1)}^{-1} - \lambda_{rn}^{-1}$, $\lambda_{s1(n-1)}$ is the desired wavelength of energy created by the system in the (N-1)th section of the fiber, and (c/λ_{rn}) is the Raman Stokes shift frequency for the active material in the Nth section of the fiber. Another reflector in section N is designed to reflect substantially all (e.g., about 100%) energy propagating in the Nth section at λ_{s1n} . The other reflector in section N is designed to reflect substantially all (e.g., about 100%) energy propagating in the Nth section at $\lambda_{s1(n-1)}$ (i.e., the desired wavelength of energy created by the system in the (N-1)th section of the fiber), where $\lambda_{s1(n-1)}^{-1} = \lambda_{s1(n-2)}^{-1} - \lambda_{r(n-1)}^{-1}$, $\lambda_{s1(n-2)}$ is the desired wavelength of energy created by the system in the (N-2)th section of the fiber, and $(c/\lambda_{r(n-1)})$ is the Raman Stokes shift frequency for the active material in the (N-1)th section of the fiber.

For any remaining sections of fiber (generically referred to as the Mth section of fiber, where M is an integer greater than one and less than N), each section has two reflectors. One reflector is designed to reflect substantially all (e.g., about 100%) energy propagating in the Mth section at wavelength λ_{s1m} (i.e., the desired wavelength of energy created by the system in the Mth section of the fiber), where $\lambda_{s1m}^{-1} = \lambda_{s1(m-1)}^{-1} - \lambda_{rm}^{-1}$, $\lambda_{s1(m-1)}$ is the desired wavelength of energy created by the system in the (M-1)th section of the fiber, and (c/λ_{rm}) is the Raman Stokes shift frequency for the active material in the Mth

section of the fiber. The other reflector is designed to reflect substantially all (e.g., about 100%) energy propagating in the M^{th} section at wavelength $\lambda_{s1(m-1)}$ (i.e., the desired wavelength of energy created by the system in the $(M-1)^{\text{th}}$ section of the fiber), where $\lambda_{s1(m-1)}^{-1} = \lambda_{s1(m-2)}^{-1} - \lambda_{r(m-1)}^{-1}$, $\lambda_{s1(m-2)}$ is the desired wavelength of energy created by the system in the $(M-2)^{\text{th}}$ section of the fiber and $(c/\lambda_{r(m-1)})$ is the Raman Stokes shift frequency for the active material in the $(M-1)^{\text{th}}$ section of the fiber.

Each section of fiber can optionally include a suppressor (e.g., an LPG with a resonance frequency corresponding to energy at an undesired higher order Raman Stokes shift energy).

The system can optionally include a reflector designed to reflect substantially all (e.g., about 100%) energy impinging thereon at wavelength λ_p .

While certain embodiments of a Raman fiber laser having N sections of optical fiber have been described, it is to be understood that the invention is not limited to these embodiments. For example, the relative positioning of the reflectors and/or suppressor(s) can be modified (e.g., in a similar manner to that noted above). Other embodiments are also contemplated.

Generally, an optical fiber having N sections can convert energy entering the optical fiber at a particular wavelength (e.g., λ_p) to energy exiting the optical fiber at a different (e.g., wavelength λ_{s1n} , where λ_{s1n} is the desired wavelength of energy created by the system in the N^{th} section of the fiber) with relatively high efficiency. In certain embodiments, fiber 110 can convert at least about 55% (e.g., at least about 60%, at least about 65%, at least about 70%, at least about 75%, at least about 80%, at least about 85%, at least about 90%, at least about 95%, at least about 98%) of the energy entering fiber 110 at one wavelength (e.g., λ_p) to energy exiting fiber 110 at a different wavelength (e.g., λ_{s1n}).

Optical fiber 110 can convert energy entering fiber 110 at a particular wavelength (e.g., λ_p) to energy exiting fiber 110 at wavelengths other than a desired output wavelength (e.g., at wavelengths other than λ_{s1n}) with relatively low efficiency. In certain embodiments, fiber 110 can convert at most about 45% (e.g., at most about 40%, at most about 35%, at most about 30%, at most about 25%, at most about 20%, at most about

15%, at most about 10%, at most about 5%, at most about 2%) of the energy entering fiber 110 at a particular wavelength (λ_p) to energy exiting fiber 110 at wavelengths other than a desired wavelength (e.g., λ_{sin}).

While certain embodiments have been described, the invention is not limited to these embodiments. For example, one or more sections of an optical fiber can be substantially devoid of a gain medium having an active material. As a further example, the reflectors need not be in the form of fiber Bragg gratings. For example, one or more of the reflectors can be a loop mirror, or one or more reflectors can be in the form of a coated mirror (e.g., a coated mirror at one or both ends of a section of optical fiber). As another example, the suppressor(s) need not be in the form of LPG(s). For example, one or more of the suppressors can be in the form of gratings (e.g., short period gratings) that are substantially nonperpendicular to the length of the fiber along which energy propagates. In these embodiments, the angle and/or period of the gratings can be selected to scatter one or more wavelengths of interest (e.g., one or more higher order Raman Stokes shift wavelengths). As an additional example, the type of laser used for pumping can be varied. Examples of lasers that can be used include semiconductor diode lasers (e.g., high-power semiconductor diode lasers), double clad doped fiber lasers, conventional free space coupled lasers, and the like. As another example, various types of optical fibers can be used, including, for example, double clad optical fibers and polarization maintaining optical fibers. Furthermore, the optical fibers can be formed of, for example, silica based materials (e.g., fused silica based) or fluoride-based materials. As yet another example, the relative and/or absolute lengths of one or more of the sections of the optical fiber can be varied based upon the intended use of the Raman fiber laser.

Moreover, while the fibers and systems have been described as Raman fiber lasers and Raman fiber laser systems, those skilled in the art will appreciate that the general concepts described can be extended to provide amplifiers and amplifier systems. Generally, a fiber amplifier provides gain for energy at a wavelength of interest without the use of a lasing cavity (e.g., without a resonator) or with an optical cavity operating below lasing threshold. Fig. 14 is a schematic view of an embodiment of a fiber

amplifier system 1400 in which fiber 1500 is used as a signal amplifier. Fiber 1500 contains multiple sections (e.g., as described above but having at least one section, such as the section adjacent the signal output, operating below lasing threshold). To operate at below lasing threshold, for example, one or more of the reflectors can be removed from fiber 1500 and/or the reflectivity of one or more of the reflectors can be reduced. An input signal enters system 1400 via fiber 1101. Energy source 1201 emits a pump signal 1301. The input signal in fiber 1101 and pump signal 1301 are coupled into fiber 1500 via coupler 1401. Such couplers are known to those skilled in the art. Pump signal 1301 interacts with the active material(s) in the sections of fiber 1500, and the input signal is amplified. A device 1900 (e.g., an isolator) separates the amplified input signal from the Stokes shifted pump signal so that the Stokes shifted pump signal travels along fiber 1800, and the amplified input signal travels along fiber 1950. While Fig. 14 shows one embodiment of fiber 1500 in a fiber amplifier system, other fiber amplifier systems in which fiber 1500 can be used will be apparent to those of skill in the art.

Other embodiments are in the claims.

What is claimed is:

Claims

1. A fiber, comprising:
an optical fiber having a first section and a second section coupled to the first section, the first section having a gain medium including a first active material and the second section having a gain medium including a second active material;
a first reflector disposed in the first section of the optical fiber, the first reflector being configured to reflect substantially all energy impinging thereon at a first wavelength; and
a second reflector disposed in the optical fiber outside the first section of the optical fiber, the second reflector being configured to reflect substantially all energy impinging thereon at the first wavelength.
2. The fiber of claim 1, wherein the first active material is the same as the second active material.
3. The fiber of claim 1, wherein the first active material is different than the second active material.
4. The fiber of claim 1, wherein the first and second sections are spliced together.
5. The fiber of claim 4, wherein the first reflector comprises a fiber Bragg grating.
6. The fiber of claim 3, wherein the second reflector comprises a fiber Bragg grating.
7. The fiber of claim 6, wherein the first active material comprises GeO_2 .

8. The fiber of claim 7, wherein the second active material comprises P_2O_5 .
9. The fiber of claim 1, wherein the second reflector comprises a fiber Bragg grating.
10. The fiber of claim 1, wherein the first active material comprises GeO_2 .
11. The fiber of claim 10, wherein the second active material comprises P_2O_5 .
12. The fiber of claim 1, wherein the first active material comprises P_2O_5 .
13. The fiber of claim 1, further comprising a third reflector disposed in the optical fiber.
14. The fiber of claim 13, wherein the third reflector comprises a fiber Bragg grating.
15. The fiber of claim 13, wherein the third reflector is disposed outside the first section of the optical fiber.
16. The fiber of claim 15, wherein the third reflector is between the first and second reflectors.
17. The fiber of claim 13, wherein the third reflector is configured to partially reflect energy impinging thereon at a second wavelength different than the first wavelength.
18. The fiber of claim 13, wherein the first and second sections are spliced together.

19. The fiber of claim 13, further comprising a fourth reflector disposed in the optical fiber.

20. The fiber of claim 19, wherein the fourth reflector comprises a fiber Bragg grating.

21. The fiber of claim 19, wherein the fourth reflector is disposed outside the first section of the optical fiber:

22. The fiber of claim 21, wherein the fourth reflector is between the first and third reflectors.

23. The fiber of claim 19, wherein the fourth reflector is configured to reflect substantially all energy impinging thereon at the second wavelength.

24. The fiber of claim 19, wherein the fourth reflector is disposed in the first section of the optical fiber.

25. The fiber of claim 19, wherein the first and second sections are spliced together.

26. The fiber of claim 19, further comprising a fifth reflector disposed in the optical fiber.

27. The fiber of claim 26, wherein the fifth reflector comprises a fiber Bragg grating.

28. The fiber of claim 26, wherein the fifth reflector is disposed in the first section of the optical fiber.

29. The fiber of claim 28, wherein the fifth reflector is between the first and fourth reflectors.
30. The fiber of claim 26, wherein the fifth reflector is configured to reflect substantially all energy impinging thereon at a second wavelength different than the first wavelength
31. The fiber of claim 26, wherein the first and second sections are spliced together.
32. The fiber of claim 26, further comprising a suppressor disposed in the optical fiber, the suppressor being capable of substantially suppressing the propagation of energy within the optical fiber at a wavelength corresponding to a higher order Raman shift wavelength than the first wavelength.
33. The fiber of claim 32, wherein the suppressor is disposed in the first section of the optical fiber.
34. The fiber of claim 33, wherein the suppressor is between the first and fifth reflectors.
35. The fiber of claim 32, wherein the suppressor comprises long period gratings.
36. The fiber of claim 32, wherein the first and second sections are spliced together.
37. The fiber of claim 32, wherein the first active material comprises GeO_2 .
38. The fiber of claim 38, wherein the second active material comprises P_2O_5 .

39. The fiber of claim 32, wherein the second active material comprises P_2O_5 .
40. The fiber of claim 1, further comprising a third reflector disposed in the first section of the optical fiber and between the first and second reflectors, the third reflector being configured to reflect substantially all energy impinging thereon at a second wavelength different than the first wavelength.
41. The fiber of claim 1, further comprising a suppressor disposed in the first section of the optical fiber and between the first and second reflectors, the suppressor being capable of substantially suppressing the propagation of energy within the optical fiber at a wavelength corresponding to a higher order Raman shift wavelength than the first wavelength.
42. The fiber of claim 41, wherein the suppressor comprises long period gratings.
43. The fiber of claim 1, wherein the first and second sections of the optical fiber are contiguous.
44. The fiber of any of the preceding claims, wherein the fiber is configured to be a fiber laser.
45. The fiber of any of claims 1-43, wherein the fiber is configured to be a fiber amplifier.
46. A system, comprising:
an energy source capable of emitting energy at a pump wavelength; and
a fiber, comprising:

an optical fiber having a first section and a second section coupled to the first section; the first section having a gain medium including a first active material and the second section having a gain medium including a second active material;

a first reflector disposed in the first section of the optical fiber, the first reflector being substantially totally reflective at a first wavelength; and

a second reflector disposed in the optical fiber outside the first section of the optical fiber, the second reflector being substantially totally reflective at a second wavelength,

wherein the energy source and the optical fiber are configured so that energy at the pump wavelength emitted by the energy source can be coupled into the optical fiber.

47. The system of claim 46, wherein the energy source comprises a laser.

48. The system of claim 47, wherein the energy source is capable of lasing at the pump wavelength.

49. The system of claim 46, wherein the first material is the same as the second material.

50. The system of claim 46, wherein the first active material is different than the second active material.

51. The system of any of claims 46-50, wherein the fiber is configured to be a fiber laser.

52. The system of any of claims 46-50, wherein the fiber is configured to be a fiber amplifier.

53. A fiber, comprising:

an optical fiber having a first section and a second section spliced to the first section, the first section having a gain medium including a first active material and the second section having a gain medium including a second active material different than the first active material;

a first reflector disposed in the first section of the optical fiber, the first reflector being configured to reflect substantially all energy impinging thereon at a first wavelength;

a second reflector disposed in the second section of the optical fiber, the second reflector being configured to reflect substantially all energy impinging thereon at the first wavelength;

a third reflector disposed in the second section of the optical fiber, the third reflector being configured to partially reflect energy impinging thereon at a second wavelength different than the first wavelength; and

a fourth reflector disposed in the second section of the optical fiber and between the first and third reflectors, the fourth reflector being configured to reflect substantially all energy impinging thereon at the second wavelength.

54. The fiber of claim 53, further comprising a fifth reflector in the first section of the optical fiber and between the first and fourth reflectors, the fifth reflector being the third reflector being configured to reflect substantially all energy impinging thereon at a third wavelength different than the first and second wavelengths.

55. The fiber of claim 54, further comprising a suppressor in the first section of the optical fiber and between the first and fifth reflectors, the suppressor being capable of substantially suppressing the propagation of energy within the optical fiber at a wavelength corresponding to a higher order Raman shift wavelength than the first wavelength.

56. The fiber of claim 55, wherein the first active material comprises P_2O_5 .

57. The fiber of claim 55, wherein the first active material comprises GeO_2 .
58. The fiber of claim 57, wherein the second active material comprises P_2O_5 .
59. The fiber of claim 58, wherein the first and second sections of the optical fiber are spliced together.
60. The fiber of claim 58, wherein the first and second sections of the optical fiber are contiguous.
61. The fiber of claim 53, further comprising a suppressor in the first section of the optical fiber and between the first and fifth reflectors, the suppressor being capable of substantially suppressing the propagation of energy within the optical fiber at a wavelength corresponding to a higher order Raman shift wavelength than the first wavelength.
62. The fiber of claim 53, wherein the first active material comprises GeO_2 .
63. The fiber of claim 62, wherein the second active material comprises P_2O_5 .
64. The fiber of claim 53, wherein the first active material comprises P_2O_5 .
65. The fiber of claim 64, wherein the second active material comprises GeO_2 .
66. The fiber of claim 53, wherein the first and second sections of the optical fiber are spliced together.
67. The fiber of claim 53, wherein the first and second sections of the optical fiber are contiguous.

68. The system of any of claims 53-67, wherein the fiber is configured to be a fiber laser.
69. The system of any of claims 53-67, wherein the fiber is configured to be a fiber amplifier.
70. A fiber laser system, comprising:
an energy source capable of emitting energy at a pump wavelength; and
a fiber, comprising:
an optical fiber having a first section and a second section spliced to the first section, the first section having a gain medium including a first active material and the second section having a gain medium including a second active material different than the first active material;
a first reflector disposed in the first section of the optical fiber, the first reflector being configured to reflect substantially all energy impinging thereon at a first wavelength;
a second reflector disposed in the second section of the optical fiber, the second reflector being configured to reflect substantially all energy impinging thereon at the first wavelength;
a third reflector disposed in the second section of the optical fiber, the third reflector being configured to partially reflect energy impinging thereon at a second wavelength different than the first wavelength; and
a fourth reflector disposed in the second section of the optical fiber and between the first and third reflectors, the fourth reflector being configured to reflect substantially all energy impinging thereon at the second wavelength
wherein the energy source and the optical fiber are configured so that energy at the pump wavelength emitted by the energy source can be coupled into the optical fiber.
71. The system of claim 64, wherein the energy source comprises a laser.

72. The system of claim 65, wherein the energy source is capable of lasing at the pump wavelength.

73. The system of any of claims 70-72, wherein the fiber is configured to be a fiber laser.

74. The system of any of claims 70-72, wherein the fiber is configured to be a fiber amplifier.

75. A fiber, comprising:
an optical fiber having N sections, the N sections being coupled together,
at least one of the N sections of the optical fiber having a gain medium with an active material; and
a plurality of reflectors disposed in the optical fiber,
wherein N is an integer having a value of at least three.

76. The fiber of claim 75, wherein N is three.

77. The fiber of claim 75, wherein N is four.

78. The fiber of claim 75, wherein N is five.

79. The fiber of claim 75, wherein N is six.

80. The fiber of claim 75, wherein at least two of the N sections of the optical fiber have a gain medium with an active material.

81. The fiber of claim 80, wherein the active material in one of the at least two of the N sections of the optical fiber is different than an active material of another of the N sections of the optical fiber having a gain medium.

82. The fiber of claim 75, wherein each of the N sections of the optical fiber have a gain medium with an active material.

83. The fiber of claim 75, wherein the optical fiber has a first section with an end configured to receive energy at a wavelength λ_p , the first section of the optical fiber having a first reflector disposed therein, the first reflector being configured to reflect substantially all energy impinging thereon at a wavelength λ_{s1} , where $\lambda_{s1}^{-1} = \lambda_p^{-1} - \lambda_{r1}^{-1}$, (c/λ_{r1}) is the Raman Stokes shift frequency for an active material in a gain medium in the first section of the optical fiber, and c is the speed of light.

84. The fiber of claim 83, wherein the optical fiber has an N^{th} section with an end opposite the end of the first section, the N^{th} section of the optical fiber having a first reflector disposed therein, the first reflector being configured to reflect substantially all energy impinging thereon at a wavelength λ_{s1n} , where $\lambda_{s1n}^{-1} = \lambda_{s1(n-1)}^{-1} - \lambda_{rn}^{-1}$, and (c/λ_{rn}) is the Raman Stokes shift frequency for an active material in a gain medium in the N^{th} section of the optical fiber.

85. The fiber of claim 84, wherein the N^{th} section of the optical fiber has a second reflector disposed therein, the second reflector being configured to partially reflect energy impinging thereon at the wavelength λ_{s1n} .

86. The fiber of claim 85, wherein the N^{th} section of the optical fiber has a third reflector disposed therein, the third reflector being configured to reflect substantially all energy impinging thereon at the wavelength $\lambda_{s1(n-1)}$, where $\lambda_{s1(n-1)}^{-1} = \lambda_{s1(n-2)}^{-1} - \lambda_{r(n-1)}^{-1}$, and $(c/\lambda_{r(n-1)})$ is the Raman Stokes shift frequency for the active material in the $(N-1)^{\text{th}}$ section of the fiber.

87. The fiber of claim 86, wherein each of the remaining sections of the optical fiber has two reflectors disposed therein, one of the reflectors disposed in each of

the remaining sections of the optical fiber being configured to reflect substantially all energy impinging thereon at a wavelength λ_{slm} , where $\lambda_{slm}^{-1} = \lambda_{sl(m-1)}^{-1} - \lambda_{rm}^{-1}$, $\lambda_{sl(m-1)}$, and (c/λ_{rm}) is the Raman Stokes shift frequency for an active material in the section of the fiber.

88. The fiber of claim 87, wherein the other of the reflectors disposed in each of the remaining sections of the optical fiber is configured to reflect substantially all energy impinging thereon at a wavelength $\lambda_{sl(m-1)}$, where $\lambda_{sl(m-1)}^{-1} = \lambda_{sl(m-2)}^{-1} - \lambda_{r(m-1)}^{-1}$, and $(c/\lambda_{r(m-1)})$ is the Raman Stokes shift frequency for an active material in an immediately preceding section of the optical fiber.

89. The fiber of claim 88, wherein each of the remaining sections of the optical fiber has two reflectors disposed therein, one of the reflectors disposed in each of the remaining sections of the optical fiber being configured to reflect substantially all energy impinging thereon at a wavelength λ_{slm} , where $\lambda_{slm}^{-1} = \lambda_{sl(m-1)}^{-1} - \lambda_{rm}^{-1}$, $\lambda_{sl(m-1)}$, and (c/λ_{rm}) is the Raman Stokes shift frequency for an active material in the section of the fiber.

90. The fiber of claim 89, wherein the other of the reflectors disposed in each of the remaining sections of the optical fiber is configured to reflect substantially all energy impinging thereon at a wavelength $\lambda_{sl(m-1)}$, where $\lambda_{sl(m-1)}^{-1} = \lambda_{sl(m-2)}^{-1} - \lambda_{r(m-1)}^{-1}$, and $(c/\lambda_{r(m-1)})$ is the Raman Stokes shift frequency for an active material in an immediately preceding section of the optical fiber.

91. The fiber of any of claims 75-90, wherein the fiber is configured to be a fiber laser.

92. The fiber of any of claims 75-90, wherein the fiber is configured to be a fiber amplifier.

93. A fiber system, comprising:

an energy source; and

a fiber, comprising:

an optical fiber having N sections, the N sections being coupled together, at least one of the N sections of the optical fiber having a gain medium with an active material; and

a plurality of reflectors disposed in the optical fiber,

wherein N is an integer having a value of at least three, and the energy source and the optical fiber are configured so that energy at a wavelength emitted by the energy source can be coupled into the optical fiber.

94. The system of claim 93, wherein the fiber is configured to be a fiber laser.

95. The system of claim 93, wherein the fiber is configured to be a fiber amplifier.

96. A fiber laser, comprising:

an optical fiber having at least first and second sections coupled together, the first section having a first gain medium with a first active material, the second section having a second gain medium with a second active material, the optical fiber being configured to be capable of receiving energy at a first wavelength and to be capable of outputting energy at a second wavelength longer than the first wavelength; and

a plurality of reflectors disposed in the optical fiber, the plurality of optical fibers being configured so that energy propagating in the optical fiber at the first wavelength undergoes at least one Raman Stokes shift to create energy in the optical fiber at the second wavelength, and so that, when the optical fiber receives energy at the first energy, a power output by the optical fiber at the second wavelength is at least about 55% of a power of the energy the optical fiber receives at that first wavelength.

97. The fiber laser of claim 96, wherein the first active material is the same as the second active material.

98. The fiber laser of claim 96, wherein the first active material is different than the second active material.

99. The fiber laser of claim 96, wherein energy propagating in the optical fiber at the first wavelength undergoes at least two Raman Stokes shifts to create energy in the optical fiber at the second wavelength.

100. The fiber laser of claim 96, wherein, when the optical fiber receives energy at the first energy, a power output by the optical fiber at wavelengths other than the first and second wavelengths is at most about 45% of the power of the energy the optical fiber receives at that first wavelength.

101. The fiber laser of claim 96, wherein the first and second sections are directly coupled together.

102. The fiber laser of claim 96, wherein the first and second sections are spliced together.

103. The fiber laser of claim 96, wherein energy propagating in the optical fiber at the first wavelength undergoes a Raman Stokes shift based interaction with the active material contained in the gain medium of the first section of the optical fiber to form energy at a first intermediate wavelength, and energy at the first intermediate wavelength undergoes a Raman Stokes shift based on interaction with the active material contained in the gain medium of the second section of the optical fiber to form a second intermediate wavelength.

104. The fiber laser of claim 103, wherein the second intermediate wavelength is the same as the second wavelength.

105. The fiber laser of claim 103, wherein energy propagating in the optical fiber at the second intermediate wavelength undergoes additional Raman Stokes shifts to form energy at the second wavelength.

106. An article, comprising:
an optical fiber having multiple sections, with at least two of the multiple sections having gain media containing different active materials.

107. The article of claim 106, wherein the optical fiber is configured as a fiber amplifier.

108. The article of claim 106, wherein the optical fiber is configured as a fiber laser.

109. A system, comprising:
an energy source capable of emitting energy at a pump wavelength; and
a fiber amplifier, comprising:
an optical fiber having a first section and a second section coupled to the first section; the first section having a gain medium including a first active material and the second section having a gain medium including a second active material,
wherein the energy source and the optical fiber are configured so that energy at the pump wavelength emitted by the energy source can be coupled into the optical fiber.

110. The system of claim 109, wherein the first active material is the same as the second active material.

111. The system of claim 110, wherein the first active material is different than the second active material.
112. The system of claim 110, wherein the energy source comprises a laser.
113. The system of claim 112, wherein the energy sources is capable of lasing at the first wavelength.
114. A fiber amplifier, comprising:
an optical fiber having N sections, the N sections being coupled together, at least one of the N sections of the optical fiber having a gain medium with an active material,
wherein N is an integer having a value of at least three.
115. The fiber amplifier of claim 114, wherein N is three.
116. The fiber amplifier of claim 114, wherein N is four.
117. The fiber amplifier of claim 114, wherein N is five.
118. The fiber amplifier of claim 114, wherein N is six.
119. The fiber amplifier of claim 114, wherein at least two of the N sections of the optical fiber have a gain medium with an active material.
120. The fiber amplifier of claim 119, wherein the active material in one of the at least two of the N sections of the optical fiber is different than an active material of another of the N sections of the optical fiber having a gain medium.

121. The fiber amplifier of claim 114, wherein each of the N sections of the optical fiber have a gain medium with an active material.

1/10




FIG. 1




FIG. 4

2/10




FIG. 2B




FIG. 2A

3/10




FIG. 3A

4/10




FIG. 3B




FIG. 3C

6/10




FIG. 5

\hat{f}




FIG. 6




FIG. 7




FIG. 8

8/10




FIG. 9




FIG. 10




FIG. 11




FIG. 12

10/10




FIG. 13




FIG. 14

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US02/14992

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : H01S 3/30

US CL : 359/346

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 359/346

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
US EAST database search terms: fiber near reflector, Raman-Stokes, "cascaded raman resonator"

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X,E	US 6,407,855 B1 (MACCORMACK et al.) 18 June 2002 (18.06.2002), column 5 line3-column 6 line 24, column 9 lines 3-29.	1-121

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T"

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X"

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y"

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&"

document member of the same patent family

Date of the actual completion of the international search

15 August 2002 (15.08.2002)

Date of mailing of the international search report

23 SEP 2002

Name and mailing address of the ISA/US

Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703)305-3230

Authorized officer

Rodney Bovernick

Telephone No. (703) 308-0956

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☒ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.